

## CERTIFICATE OF CONSTANCY OF PERFORMANCE

### 1239/CPR/0816308

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it's certified that the

Construction product: **Building hardware. Panic exit devices operated by a horizontal bar, for use on escape routes**

Scope of Certification:  
(references): **RIM PANIC EXIT DEVICE**  
*References included in each of the certified series are listed in the annex of this certificate*

Product classification:

<b>3</b>	<b>7</b>	<b>6</b>	<b>0</b>	<b>1</b>	<b>3</b>	<b>2</b>	<b>1</b>	<b>A</b>	<b>A</b>
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)

Provided and Produced by: **DOM-MCM, S.A.**  
**C/ Artapadura, nº 12**  
**01013 VITORIA (Araba) SPAIN**

Is subject to a factory production control and to the inspection of samples in accordance to a prescribed test plan by the manufacturer, and that the Notified Body TECNALIA R&I CERTIFICACION S.L. has carried out initial type tests for all relevant characteristics of the product, as well as the initial inspection of the factory and FPC, and the continuous surveillance, assessment and approval of FPC.

This certificate shows compliance with all regulations applicable to the conformity assessment in the Annex ZA of the standard

### EN 1125:2008

and that the product meets the minimum requirements applicable.

System of assessment and verification of constancy of performance: **SYSTEM 1**

**Issued on:** 18/12/2013  
**Last modified on:** 25/11/2022  
**Expires on:** 15/12/2025  
**Serial no:** 081630809-E

This document allows the manufacturer to fix the CE mark.  
This certificate may be modified, temporarily suspended and withdrawn by TECNALIA R&I CERTIFICACION.  
The validity of this certificate can be checked through consultation in [www.tecnaliacertificacion.com](http://www.tecnaliacertificacion.com).



## ANNEX CERTIFICATE OF CONSTANCY OF PERFORMANCE 1239/CPR/0816308

### Construction product:

Panic exit devices operated by a horizontal bar, for use on escape routes

Reference	Description
B110/BP110	1 point locking panic exit device, for use on single leaf doors or on the active leaf in double doorsets.
B112/BP112	1 point locking panic exit device, for use on single leaf doors or on the active leaf in double doorsets.
B120/BP120	Vertical panic exit device, for use on single leaf doors or on the inactive leaf in double doorsets.
Surface finish: NR (Black/Red), BB (White), NM (dull Nickel-plated), II (dull Stainless steel), OO (Gold-plated), CC (Chrome-plated), NN (Black), PP (Silver), NI (Black/ Stainless steel bar), NMI (dull Nickel / Stainless steel bar), NV (Black/ Green bar) and NAM (Black/ yellow bar).	
Case: B (Metallic) and BP (Plastic).	