

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1239/CPR/0801703

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it's certified that the

Construction product: Building hardware. Locks and latches. Mechanically operated

locks, latches and locking plates.

Scope of Certification: 1901 (H, E, ERL, T)

(references) References included in each of the certified series are listed in the annex of

this certificate.

Product classification: see Annex

Provided and Produced by: **DOM-MCM, S.A.**

C/ Artapadura, nº 12

01013 VITORIA (Araba) SPAIN

Is subject to a factory production control and to the inspection of samples in accordance to a prescribed test plan by the manufacturer, and that the Notified Body TECNALIA R&I CERTIFICACION S.L. has carried out initial type tests for all relevant characteristics of the product, as well as the initial inspection of the factory and FPC, and the continuous surveillance, assessment and approval of FPC

This certificate shows compliance with all regulations applicable to the conformity assessment in the Annex ZA of the standard

EN 12209:2003 + EN 12209:2003/AC:2005

and that the product meets the minimum requirements applicable. Those digits identified with * are referred to the essential characteristics shown in table ZA.1 of the standard and therefore are the only ones covered by ENAC's accreditation.

System of assessment and verification of constancy of performance: SYSTEM 1

 Issued on:
 30/11/2007

 Last modified on:
 22/01/2024

 Expires on:
 28/02/2026

Serial no: 080170314-E

Carlos Nazabal Alsua Manager



This certificate may be modified, temporarily suspended and withdrawn by TECNALIA R&I CERTIFICACION.

The validity of this certificate can be checked through consultation in www.tecnaliacertificacion.com.





ANNEX CERTIFICATE OF CONSTANCY OF PERFORMANCE 1239/CPR/0801703

Construction product: Mechanically operated locks.

References	Der	nomination
1901 (H, E, ERL, T)	follo	hanical lock with bolt and split follower (E,T) or through ower (H, ERL): With dead-locking latch Backset: 60 or 70 mm Forend of 23mm width and 3mm thickness, brass plated steel or stainless steel. Steel latch With dead-bolt Striking plate 1601/1601M/1901H in brass plated steel or gold-painted steel.

According to the initial type-tests, the classification of the devices is as follows:

	Digit 1	Digit 2	Digit 3	Digit 4	Digit 5	Digit 6	Digit 7	Digit 8	Digit 9	Digit 10	Digit 11
BACKSET 60 mm	3*	M*	8*	1*	0	С	1	В	A	2	0
BACKSET 70 mm	3*	M*	8*	1*	0	С	1	В	С	2	0

Digit 1 – Category of use Digit 2 – Durability

Digit 3 – Door mass and closing force

Digit 4 – Suitability for use on fire resisting and/or smoke control door set

Digit 5 – Safety

Digit 6 – Corrosion resistence and temperature.

Digit 7 - Security and drill resistance

Digit 8 – Field of door application

Digit 9 – Type of key operation and locking

Digit 10 – Type of spindle operation

Digit 11 - Key identification

