

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1239/CPR/0801706

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products, it's certified that the

Construction product: **Building hardware. Locks and latches. Mechanically operated locks, latches and locking plates.**

Scope of Certification: **SERIE INSTITUCIONAL (SI 01F2)**
References included in each of the certified series are listed in the annex of this certificate

Product classification:

2	S	7	1	0	C	1	B	C	2	0
(1)*	(2)*	(3)*	(4)*	(5)	(6)	(7)	(8)	(9)	(10)	(11)

Provided and Produced by: **DOM-MCM, S.A.**
C/ Artapadura, nº 12
01013 VITORIA (Araba) SPAIN

Is subject to a factory production control and to the inspection of samples in accordance to a prescribed test plan by the manufacturer, and that the Notified Body TECNALIA R&I CERTIFICACION S.L. has carried out initial type tests for all relevant characteristics of the product, as well as the initial inspection of the factory and FPC, and the continuous surveillance, assessment and approval of FPC

This certificate shows compliance with all regulations applicable to the conformity assessment in the Annex ZA of the standard

EN 12209:2003 + EN 12209:2003/AC:2005

and that the product meets the minimum requirements applicable. Those digits identified with * are referred to the essential characteristics shown in table ZA.1 of the standard and therefore are the only ones covered by ENAC's accreditation.

System of assessment and verification of constancy of performance : **SYSTEM 1**



Issued on: 25/02/2010
Last modified on: 01/12/2021
Expires on: 28/02/2023
Serial no: 080170609-E

This document allows the manufacturer to fix the CE mark.

This certificate may be modified, temporarily suspended and withdrawn by TECNALIA R&I CERTIFICACION.

The validity of this certificate can be checked through its QR code or through consultation in www.tecnaliacertificacion.com.

ANNEX
CERTIFICATE OF CONSTANCY OF PERFORMANCE
1239/CPR/0801706

Construction product: Mechanically operated locks

Referencia	Denominación
SI 01F2xx0Ax11	Mechanical lock with dead-bolt and single follower: – Without dead-locking latch – Backset: 50 or 60 mm – Forend: – Straight or round Edge. – 23mm width and 3mm thickness. – In brass plated steel. – Steel latch – Striking plate SI01 in brass plated steel.